



Both single and double glazed windows can be ordered glazed or unglazed. The 'R' values shown are from NZ Standard NZS 4218:2004 for Energy Efficiency. **Please note that some size restrictions may apply to larger 'Insulite' units.**

Code: BVBFW2

Min Height: 1000mm
 Max Height: 1600mm
 Min Width: 1100mm
 Max Width: 1400mm
 'R' Value Single Glaze 0.27
 (6.38 Laminate Clear 'Low E' Glass)
 'R' Value Double Glaze 0.36
 (4mm Clear, 10 Air, 4mm Clear)





Trendlite Single Glazed

Sash: Paint Quality Cedar, 40mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: <140 x 35mm
 Sill: Standard SJ9 42mm
 Facings: <140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Stainless Steel Hinges
 Draught Seals: Aquamac White included
Glazing: Suitable for Single Glazed units up to 8.38mm thick.

Code: BVBFW3

Min Height: 1000mm
 Max Height: 1600mm
 Min Width: 1600mm
 Max Width: 2100mm
 'R' Value Single Glaze 0.27
 (6.38 Laminate Clear 'Low E' Glass)
 'R' Value Double Glaze 0.36
 (4mm Clear, 10 Air, 4mm Clear)





Insulite Double Glazed

Sash: Paint Quality Cedar, 55mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: <140 x 42mm
 Sill: Standard 42mm
 Facings: <140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Stainless Steel Hinges
 Draught Seals: Aquamac White included.
Glazing: Suitable for Double Glazed units up to 21mm thick.

Code: BVBFW4



Min Height: 1000mm
 Max Height: 1600mm
 Min Width: 2100mm
 Max Width: 2800mm
 'R' Value Single Glaze 0.27
 (6.38 Laminate Clear 'Low E' Glass)
 'R' Value Double Glaze 0.36
 (4mm Clear, 10 Air, 4mm Clear)



These doors are available as 'multi lites'. Please ask for more details



Code: BVBFW5

Min Height: 1000mm
 Max Height: 1600mm
 Min Width: 2600mm
 Max Width: 3500mm
 'R' Value Single Glaze 0.27
 (6.38 Laminate Clear 'Low E' Glass)
 'R' Value Double Glaze 0.36
 (4mm Clear, 10 Air, 4mm Clear)



Code: BVBFW6


Min Height: 1000mm
 Max Height: 1600mm
 Min Width: 3100mm
 Max Width: 4200mm
 'R' Value Single Glaze 0.27
 (6.38 Laminate Clear 'Low E' Glass)
 'R' Value Double Glaze 0.36
 (4mm Clear, 10 Air, 4mm Clear)



Both single and double glazed windows can be ordered glazed or unglazed. The 'R' values shown are from NZ Standard NZS 4218:2004 for Energy Efficiency. **Please note that some size restrictions may apply to larger 'Insulite' units.**

Code: BVSSW2

Min Height:	1000mm
Max Height:	1600mm
Min Width:	1110mm
Max Width:	3000mm
'R' Value Single Glaze	0.27
<small>(6.38 Laminated Clear 'Low E' Glass)</small>	
'R' Value Double Glaze	0.36
<small>(4mm Clear, 10 Air, 4mm Clear)</small>	




Trendlite Single Glazed

Sash:	Paint Quality Cedar, 40mm
Frame:	Paint Quality H3.2/H3.1 Pine
Jamb:	≤140 x 35mm
Sill:	Standard 42mm
Facings:	≤140x18 Flat
Prime:	1 Coat Oil Based Primer
Draught Seals:	Black Brush.
Glazing:	Suitable for Single Glazed units up to 8.38mm thick.

Code: BVSSW3

Min Height:	1000mm
Max Height:	1600mm
Min Width:	1620mm
Max Width:	3600mm
'R' Value Single Glaze	0.27
<small>(6.38 Laminated Clear 'Low E' Glass)</small>	
'R' Value Double Glaze	0.36
<small>(4mm Clear, 10 Air, 4mm Clear)</small>	




Insulite Double Glazed

Sash:	Paint Quality Cedar, 55mm
Frame:	Paint Quality H3.2/H3.1 Pine
Jamb:	≤140 x 42mm
Sill:	Standard 42mm
Facings:	≤140x18 Flat
Prime:	1 Coat Oil Based Primer
Draught Seals:	Black Brush.
Glazing:	Suitable for Double Glazed units up to 21mm thick.

Code: BVSSW4


Min Height:	1000mm
Max Height:	1600mm
Min Width:	2200mm
Max Width:	4800mm
'R' Value Single Glaze	0.27
<small>(6.38 Laminated Clear 'Low E' Glass)</small>	
'R' Value Double Glaze	0.36
<small>(4mm Clear, 10 Air, 4mm Clear)</small>	




These doors are available as 'multi lites'. Please ask for more details

Code: BVOSW1

Min Height:	1000mm
Max Height:	1600mm
Min Width:	1000mm
Max Width:	1500mm
'R' Value Single Glaze	0.27
<small>(6.38 Laminated Clear 'Low E' Glass)</small>	
'R' Value Double Glaze	0.36
<small>(4mm Clear, 10 Air, 4mm Clear)</small>	




Closed




Open

Code: BVOSW2

Min Height:	1000mm
Max Height:	1600mm
Min Width:	1200mm
Max Width:	3000mm
'R' Value Single Glaze	0.27
<small>(6.38 Laminated Clear 'Low E' Glass)</small>	
'R' Value Double Glaze	0.36
<small>(4mm Clear, 10 Air, 4mm Clear)</small>	



Closed






Open

Both single and double glazed windows can be ordered glazed or unglazed. The 'R' values shown are from NZ Standard NZS 4218:2004 for Energy Efficiency. **Please note that some size restrictions may apply to larger 'Insulite' units.**

1 'Lite' Windows


Trendlite Single Glazed

Sash: Paint Quality Cedar, 40mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: <140 x 35mm
 Sill: Standard SJ9 42mm
 Facings: <140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Stainless Steel Hinges
 Draught Seals: Aquamac White included.
Glazing: Suitable for Single Glazed units up to 8.38mm thick.

			
Code	BVCW1	BVCW2	BVCW3
Min Height	900mm	900mm	900mm
Max Height	1800mm	1800mm	1800mm
Min Width	300mm	1000mm	1500mm
Max Width	900mm	1600mm	2400mm
'R' Value - Single Glaze (6.38 Laminated Clear 'Low E' Glass)	0.27	0.27	0.27
'R' Value - Double Glaze (4mm Clear, 10 Air, 4mm Clear)	0.36	0.36	0.36

Insulite Double Glazed




Sash: Paint Quality Cedar, 55mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: <140 x 42mm
 Sill: Standard 42mm
 Facings: <140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Stainless Steel Hinges
 Draught Seals: Aquamac White included.
Glazing: Suitable for Double Glazed units up to 21mm thick.

		
Code	BVCW3.1	BVCW4
Min Height	900mm	900mm
Max Height	1800mm	1800mm
Min Width	2300mm	2420mm
Max Width	3500mm	3620mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27	0.27
'R' Value - Double Glaze (4mm Clear, 10 Air, 4mm Clear)	0.36	0.36

6 'Lite' Windows



Trendlite Single Glazed

Sash: Paint Quality Cedar, 40mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: <140 x 35mm
 Sill: Standard SJ9 42mm
 Facings: <140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Stainless Steel Hinges
 Draught Seals: Aquamac White included.
Glazing: Suitable for Single Glazed units up to 8.38mm thick.

			
Code	BVCW1C	BVCW2C	BVCW3C
Min Height	900mm	900mm	900mm
Max Height	1800mm	1800mm	1800mm
Min Width	600mm	1200mm	1800mm
Max Width	900mm	1600mm	2400mm
'R' Value - Single Glaze (6.38 Laminated Clear 'Low E' Glass)	0.27	0.27	0.27
'R' Value - Double Glaze (4mm Clear, 10 Air, 4mm Clear)	0.36	0.36	0.36

Insulite Double Glazed

Sash: Paint Quality Cedar, 55mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: <140 x 42mm
 Sill: Standard 42mm
 Facings: <140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Stainless Steel Hinges
 Draught Seals: Aquamac White included.
Glazing: Suitable for Double Glazed units up to 21mm thick.

		
Code	BVCW3.1C	BVCW4C
Min Height	900mm	900mm
Max Height	1800mm	1800mm
Min Width	2300mm	2420mm
Max Width	3500mm	3620mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27	0.27
'R' Value - Double Glaze (4mm Clear, 10 Air, 4mm Clear)	0.36	0.36

Both single and double glazed windows can be ordered glazed or unglazed. The 'R' values shown are from NZ Standard NZS 4218:2004 for Energy Efficiency. **Please note that some size restrictions may apply to larger 'Insulite' units.**




1 'Lite' Windows

Trendlite Single Glazed



Sash: Paint Quality Cedar, 40mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: < 140 x 35mm
 Sill: Standard SJ9 42mm
 Facings: < 140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Stainless Steel Hinges
 Draught Seals: Aquamac White included.
Glazing: Suitable for Single Glazed units up to 8.38mm thick.

Insulite Double Glazed

Sash: Paint Quality Cedar, 55mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: < 140 x 42mm
 Sill: Standard 42mm
 Facings: < 140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Stainless Steel Hinges
 Draught Seals: Aquamac White included.
Glazing: Suitable for Double Glazed units up to 21mm thick.



Code	BVBW1	BVBW2	BVCW3
Min Height	1400mm	1400mm	1400mm
Max Height	1800mm	1800mm	1800mm
Min Width	460mm	1100mm	1660mm
Max Width	710mm	1410mm	2110mm
'R' Value - Single Glaze (6.38 Laminated Clear 'Low E' Glass)	0.27	0.27	0.27
'R' Value - Double Glaze (4mm Clear, 10 Air, 4mm Clear)	0.36	0.36	0.36



Code	BVBW3.1	BVBW4
Min Height	1400mm	1400mm
Max Height	1800mm	1800mm
Min Width	2000mm	2200mm
Max Width	2500mm	2820mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27	0.27
'R' Value - Double Glaze (4mm Clear, 10 Air, 4mm Clear)	0.36	0.36

Both single and double glazed windows can be ordered glazed or unglazed. The 'R' values shown are from NZ Standard NZS 4218:2004 for Energy Efficiency. **Please note that some size restrictions may apply to larger 'Insulite' units.**


1 Lite Windows

Trendlite Single Glazed


Sash: Paint Quality Cedar, 40mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: <140 x 35mm
 Sill: Standard SJ9 42mm
 Facings: <140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Friction Stays, Black
 Draught Seals: Aquamac White included.
Glazing: Suitable for Single Glazed units up to 8.38mm thick.

Insulite Double Glazed


Sash: Paint Quality Cedar, 55mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: <140 x 42mm
 Sill: Standard 42mm
 Facings: <140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Friction Stays, Black
 Draught Seals: Aquamac White included.
Glazing: Suitable for Double Glazed units up to 21mm thick.




Code	BVAW1
Min Height	600mm
Max Height	1800mm
Min Width	300mm
Max Width	900mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27




Code	BVAW2
Min Height	600mm
Max Height	1800mm
Min Width	1000mm
Max Width	1600mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27



Code	BVAW3
Min Height	600mm
Max Height	1800mm
Min Width	1500mm
Max Width	2400mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27



Code	BVAW3.1
Min Height	600mm
Max Height	1800mm
Min Width	2300mm
Max Width	3500mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27



Code	BVAW4
Min Height	600mm
Max Height	1800mm
Min Width	2420mm
Max Width	3620mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27


6 Lite Windows

Trendlite Single Glazed


Sash: Paint Quality Cedar, 40mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: <140 x 35mm
 Sill: Standard SJ9 42mm
 Facings: <140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Friction Stays, Black
 Draught Seals: Aquamac White included.
Glazing: Suitable for Single Glazed units up to 8.38mm thick.

Insulite Double Glazed


Sash: Paint Quality Cedar, 55mm
 Frame: Paint Quality H3.2/H3.1 Pine
 Jamb: <140 x 42mm
 Sill: Standard 42mm
 Facings: <140x18 Flat
 Prime: 1 Coat Oil Based Primer
 Hardware: Friction Stays, Black
 Draught Seals: Aquamac White included.
Glazing: Suitable for Double Glazed units up to 21mm thick.




Code	BVAW1C
Min Height	900mm
Max Height	1800mm
Min Width	300mm
Max Width	900mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27




Code	BVAW2C
Min Height	900mm
Max Height	1800mm
Min Width	1000mm
Max Width	1600mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27



Code	BVAW3C
Min Height	900mm
Max Height	1800mm
Min Width	1500mm
Max Width	2400mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27



Code	BVAW3.1C
Min Height	900mm
Max Height	1800mm
Min Width	2300mm
Max Width	3500mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27



Code	JSAW4C
Min Height	900mm
Max Height	1800mm
Min Width	2420mm
Max Width	3620mm
'R' Value (6.38 Clear Laminated Low E Glass)	0.27